

In the claims:

Please amend the claims as follows:

1. (Original) A golf shoe cleat comprising a body member having an outer face and an inner face, shoe mounting member having an axis AL which is perpendicular to said inner face and projecting outwardly from said inner face and adapted to secure said, cleat in a receptacle in said golf shoe upon rotation of said shoe mounting member in said receptacle,

a circular array of shaped traction teeth projecting outwardly around the perimeter of said outer face, each traction tooth having an axis ALT and an outer traction tooth surface, each outer traction tooth surface and axis ALT having an outward angulation relative to said axis AL to provide lateral stability and enhanced traction through the plane of a golf swing and wherein said inner face has a peripheral edge spaced from said shoe mounting member and an anti-debris ring formed integrally with said body member and projecting from said inner face.

2. (Original) A golf shoe cleat comprising a main body member having a dome-shaped outer face and a planar inner face, a shoe attaching member projecting outwardly from said planar inner face having an axis AL perpendicular to said planar inner face,

a circular array of shaped traction teeth projecting around the perimeter of said main body member, each traction tooth having an axis ALT, said axis ALT having an outward angulation relative to said axis AL to provide lateral stability and traction through the plane of a golf swing, said outward angulation being about $37\frac{1}{2}^{\circ}$.

3. (Original) A golf shoe cleat comprising a body member having an outer face and an inner face, shoe mounting member having an axis AL which is perpendicular to said inner face and projecting outwardly from said inner face and adapted to secure said cleat in a receptacle in said golf shoe upon rotation of said shoe mounting member about said axis in said receptacle,

a circular array of low profile traction teeth projecting outwardly around the perimeter of said outer face, each traction tooth having a traction surface which faces away from said axis AL, each traction tooth having an axis ALT and each axis ALT having an outward angulation relative to said axis AL to provide lateral stability and enhanced traction through the plane of a golf swing.

4. (Original) The cleat defined in claim 3 wherein said inner face has a peripheral edge spaced from said shoe mounting member and an anti-debris ring formed integrally with said body member and projecting from said inner face.

5. (Original) A golf shoe cleat comprising a main body member having a dome-shaped outer face and a planar inner face, a shoe attaching member projecting outwardly from said inner face having an axis AL perpendicular to said planar inner face and adapted to secure said cleat in a receptacle in said golf shoe upon rotation of said shoe mounting member in said receptacle,

an annular anti-debris ring formed on the edge of said planar inner face,

a plurality of shaped traction teeth projecting in a circular array around the perimeter of said main body member, each traction tooth being spaced from said axis AL and having an axis ALT and an outer traction surface facing away from said axis AL, each said outer axis ALT and traction surface having an outward angulation relative to said axis AL to provide lateral stability and traction through the plane of a golf swing.

6. (Original) A golf shoe cleat comprising a main body member having a dome-shaped outer face and a planar inner face, shoe attachment means having an axis AL, said shoe attachment means projecting outwardly from said inner face and adapted to secure said cleat in a receptacle in said golf shoe upon rotation of said shoe mounting member in said receptacle,

a plurality of pseudo pyramid-shaped teeth projecting around the perimeter of said main body member, each pseudo pyramid-shaped tooth having an axis ALT and an outwardly angled traction surface which faces away from said axis AL and provides lateral stability and traction through the plane of a golf swing, said teeth being in a low profile to reduce damage to putting green surfaces,

said body member having an anti-debris ring on the peripheral edge of said planar inner face.

7. (Original) A golf shoe cleat comprising a molded main body member having a dome-shaped outer face and a planar inner face,

a mounting member projecting vertically outwardly from said inner face and having an axis AL and adapted to secure said cleat in a receptacle in said golf shoe upon rotation of said shoe mounting member in said receptacle,

said main body member having a circular perimeter,

a plurality of traction teeth circumferentially spaced around said circular perimeter of said main body member, each traction tooth having an axis ALT and an outwardly angled outer traction surface which faces away from said axis AL to provide lateral stability and traction through the plane of a golf swing.

8. (Original) The golf shoe cleat defined in claim 7 wherein said traction teeth are pseudo pyramid-shaped.

9. (Original) A golf shoe cleat comprising a main body member having an inner face and an outer face, a shoe-attaching member projecting perpendicularly outwardly from said inner face and said shoe-attaching member having an axis AL and adapted to secure said cleat in a receptacle in said golf shoe upon rotation of said shoe mounting member in said receptacle,

a plurality of low-profile traction teeth projecting around the perimeter of the outer face of said main body member in a circular array, each traction tooth having an axis ALT and outer traction surface which are angled away from said axis AL, said outer traction surface having an outward angulation relative to said axis AL to enhance lateral stability and traction through the plane of a golf swing.

10. (Original) A golf shoe cleat comprising a main body member having an inner face and an outer face, a shoe-attaching member projecting perpendicularly outwardly from said inner face and said shoe-attaching member having an axis AL and adapted to secure said cleat in a receptacle in said golf shoe upon rotation of said shoe mounting member in said receptacle,

a plurality of low-profile traction teeth projecting around the perimeter of the outer face of said main body member, each traction tooth having an outer traction surface facing away from said axis AL, said outer surface having an outward angulation relative to said axis AL to enhance lateral stability and traction through the plane of a golf swing.

11. (Amended) The golf shoe cleat defined in claim [10] 9 wherein the angle between each said tooth axis ALT and said axis AL is about 37½ degrees.

12. (New) A golf shoe cleat comprising a main body member having an inner face and an outer face, a shoe-attaching member projecting perpendicularly outwardly from said inner face and said shoe-attaching member having an axis AL and adapted to secure said cleat in a receptacle in said golf shoe upon rotation of said shoe mounting member in said receptacle,

a circular array of tapered traction teeth formed of a resilient and flexible material projecting from the perimeter of said main body member, each traction tooth having an outer traction surface extending from said main body member in a direction away from and at an angle to said axis AL to enhance lateral stability and traction through the plane of a golf swing.

13. (New) The golf shoe cleat defined in claim 12, wherein said outer face is substantially planar and said traction teeth project from said outer face.

14. (New) The golf shoe cleat defined in claim 12, wherein said outer face is dome-shaped and said traction teeth project from said outer face.

15. (New) The golf shoe cleat defined in claim 12, wherein each traction tooth has an axis ALT which is angled away from said axis AL, said axis ALT having an outward angulation relative to said axis AL to enhance said lateral stability and traction through the plane of a golf swing.

16. (New) The golf shoe cleat defined in claim 15, wherein the angle between each said tooth axis ALT and said axis AL is about $37\frac{1}{2}$ degrees.

17. (New) The golf shoe cleat defined in claim 12, wherein the traction teeth are a low-profile traction teeth.

18. (New) The golf shoe cleat as defined in claim 12, wherein the traction teeth are tapered away from the main body member.

Status of Claims and Support for Claim Changes, 37 C.F.R. §1.173(c)

1-10. Original.

11. Amended. The subject matter of claim 11 as amended finds support in the original patent, e.g., in column 3, lines 13-15.

12. New. The subject matter of claim 12 finds support in the original patent, e.g., in Figs. 1 and 2 and in the paragraph spanning columns 2 and 3, and in column 1, line 52.

13. New. The subject matter of claim 13 finds support in the original patent, e.g., in Figs. 7A and 8A.

14. New. The subject matter of claim 14 finds support in the original patent, e.g., in Fig. 2.

15. New. The subject matter of claim 15 finds support in the original patent, e.g., in column 1, lines 59-62.

16. New. The subject matter of claim 16 finds support in the original patent, e.g., in column 3, lines 13-15.

17. New. The subject matter of claim 17 finds support in the original patent, e.g., in column 3, lines 16-17.

18. New. The subject matter of claim 18 finds support in the original patent, e.g., in Figs. 1 and 2.